



SDR 35 PVC Solvent Weld Sewer Fittings Injection Molded in Sizes 3" – 12" Fabricated in Sizes 10" – 27"

Applications


Plastic Trends has the broadest product offering of Solvent Weld Sewer fittings in the industry. They conform to all municipal, federal, and military requirements. They are tested for joint tightness, internal stress and dimensional stability. The "P" Series is engineered for the harsh environment of construction, shipping, handling and installation.

Listed below are some of the uses of Solvent Weld Sewer fittings:

- Onsite Disposal
 - Closed loop septic fields
 - Open system septic fields
 - Engineered systems
- Surface Drainage
 - Foundation Drains
 - Radon Gas Venting
 - Yard Drainage
 - Downspouts
 - Pool Drainage
 - Area Drainage
 - Landscape Drainage
- Laterals to Municipal Sewers (sanitary and storm)

Certifications

Plastic Trends Solvent Weld Sewer fittings are third party tested and listed by NSF, UPC, and CSA to meet specifications defined in ASTM D 3034 and CSA B181.2.



[Solvent Weld Sewer Fittings SDR 35 Spec Sheet](#)

[Intelli \(P Series\)](#)

[Price List](#)

[Dimensional Drawings](#)

Short Form Specifications

4" through 12" injection molded solvent weld SDR 35 sewer fittings shall be manufactured in accordance with ASTM D 3034 and CSA B182.2. They shall be molded from virgin PVC compound having a minimum cell classification of 12454-B in accordance with, and certified by the National Sanitation Foundation (NSF), to meet ASTM D 1784. Solvent weld SDR 35 sewer fittings shall be certified by the National Sanitation Foundation (NSF) to meet ASTM D 3034, and, in applicable configurations, by the Canadian Standards Association (CSA) to meet CSA B182.2.

Additional Plumbing Fittings

- [Perfect Fit™ Solvent Weld DWV Fittings](#)
- [Solvent Weld Sewer Fittings SDR 35](#)